



6000SGHT WINDOW WALL PRODUCT DATA SHEET

| | | |
|--|--|--|
| DESCRIPTION | DESIGNATION SERIES CONFIGURATIONS | WINDOW WALL 6000SGHT FIXED/OPERABLE |
| AIR, WATER & STRUCTURAL TESTING | TEST SIZE ALLOWABLE AIR WATER INTER-STORY MOVEMENT | FULL SIZE MOCKUP (22' X 9') MAX 0.10 CFM/LF @ 6.24 PSF (OPERABLE) MAX 0.06 CFM/LF @ 6.24 PSF (FIXED) 15 PSF ±0.50 HORIZONTAL ±0.50 VERTICAL |
| CRF & 'U' VALUE | CRF U-VALUE | 55 – 72 0.35 – 0.58 |
| CONSTRUCTION *FRAME | MINIMUM WALL THICKNESS MINIMUM WALL THICKNESS @ FASTENERS DEPTH FABRICATION | 0.080" 0.094" 6" MITERED, MECHANICALLY FASTENED AND SEALED |
| *PRIMARY OPERABLE | STYLE MINIMUM WALL THICKNESS MINIMUM WALL THICKNESS @ FASTENERS DEPTH FABRICATION | ZERO SIGHTLINE 0.094" 0.094" 4" MITERED, EPOXIED AND CRIMPED W/ ALUMINUM CORNER BLOCKS |
| THERMAL BARRIER | SEPARATION DESIGN | 1-5/16" CUSTOM GLASS REINFORCED POLYAMIDE |
| WEATHER-STRIPPING | PRIMARY OPERABLE | (2) ROWS EPDM |
| GLAZING | LOCATION METHOD INSTALLATION | FACTORY OR FIELD 3M VHB OR STRUCTURAL SILICONE EXTERIOR GLAZED |
| SCREENS | AS SPECIFIED | FLAT OR WICKET |
| HARDWARE | AS SPECIFIED | MANUFACTURERS STANDARD |
| FINISH | AS SPECIFIED | ANODIZED OR PAINTED |
| WARRANTY | AS SPECIFIED | 2, 5, OR 10 YEARS (2 YEAR STANDARD) |