

# Signature Series 3375

## Product Data Sheet

<b>DESCRIPTION</b>	AAMA CATEGORY	ARCHITECTURAL
	AAMA DESIGNATION SERIES CONFIGURATION	AW-100 SIGNATURE 3375 FIXED PROJECTED CASEMENT
<b>AAMA AIR, WATER &amp; STRUCTURAL TESTING</b>	TEST SIZE  ALLOWABLE AIR WATER UNIFORM LOAD DEFLECTION UNIFORM LOAD STRUCTURAL	AAMA 101 FOR DESIGNATION AND/OR CONFIGURATION MAX 0.10 CFM/LF @ 6.24 PSF 15 PSF 100 PSF 150 PSF
<b>CRF &amp; 'U' VALUE</b>	CRF U-VALUE	CRF 55 – 74 U 0.30 – 0.58
<b>CONSTRUCTION</b>	MINIMUM WALL THICKNESS MINIMUM WALL THICKNESS @ SILL FRAME DEPTH DESIGN FABRICATION	0.065"  0.065" 3-3/8" EQUAL LEG MITERED, EPOXIED, & CRIMPED W/ ALUMINUM CORNER BLOCKS
<b>THERMAL BARRIER</b>	SEPARATION DESIGN	1-1/8" (2) CRIMPED IN PLACE, GLASS REINFORCED POLYAMIDE 6/6 STRIPS
<b>WEATHER-STRIPPING</b>	PRIMARY OPERABLE	(2) ROWS EPDM
<b>GLAZING</b>	LOCATION METHOD INSTALLATION	FACTORY OR FIELD WET/DRY INTERIOR GLAZED
<b>SCREENS</b>	AS SPECIFIED	FLAT OR INSIDE REMOVABLE
<b>HARDWARE</b>	AS SPECIFIED	MANUFACTURERS STANDARD
<b>FINISH</b>	AS SPECIFIED	ANODIZED OR PAINTED
<b>WARRANTY</b>	AS SPECIFIED	2, 5, OR 10 YEARS (2 YEAR STANDARD)