

Signature Series 3-1/4" Lap Product Data Sheet

DESCRIPTION	AAMA CATEGORY	ARCHITECTURAL
	AAMA DESIGNATION SERIES CONFIGURATION	AW-100 SIGNATURE 3-1/4" LAP FIXED PROJECTED CASEMENT
AAMA AIR, WATER & STRUCTURAL TESTING	TEST SIZE ALLOWABLE AIR WATER UNIFORM LOAD DEFLECTION UNIFORM LOAD STRUCTURAL	AAMA 101 FOR DESIGNATION AND/OR CONFIGURATION MAX 0.10 CFM/LF @ 6.24 PSF 15 PSF 100 PSF 150 PSF
CRF & 'U' VALUE	CRF U-VALUE	CRF 55 – 74 U 0.30 – 0.58
CONSTRUCTION	MINIMUM WALL THICKNESS MINIMUM WALL THICKNESS @ SILL FRAME DEPTH DESIGN FABRICATION	0.080" 0.080" 3-1/4" EQUAL LEG MACHINED, MECHANICALLY FASTENED AND SEALED
THERMAL BARRIER	SEPARATION DESIGN	1-3/16" (2) CRIMPED IN PLACE, GLASS REINFORCED POLYAMIDE 6/6 STRIPS
WEATHER-STRIPPING	PRIMARY OPERABLE	(2) ROWS EPDM
GLAZING	LOCATION METHOD INSTALLATION	FACTORY OR FIELD WET/DRY INTERIOR GLAZED
SCREENS	AS SPECIFIED	FLAT, SLIDING WICKET, OR HINGED
HARDWARE	AS SPECIFIED	MANUFACTURERS STANDARD
FINISH	AS SPECIFIED	ANODIZED OR PAINTED
WARRANTY	AS SPECIFIED	2, 5, OR 10 YEARS (2 YEAR STANDARD)