

MWS Interior CW/SF Series —41N

Product Data

Description

AAMA Category – Architectural

AAMA 101 Designation – None

Configuration – Lift-Off or Hinged Interior Access Panel

Series – 41N

AAMA Air, Water & Structural Testing

Test Size – N/A

Allowable Air – N/A

Water – N/A

Uniform Load Deflection – N/A

Uniform Load Structural – N/A

CRF & 'U' Value

CRF Class – N/A

U-Value Class – N/A

Construction – Frame

Minimum Wall Thickness – 0.078"

Depth – 1-3/8"

Fabrication – Mitered, Epoxied & Crimped w/Alum Corner Blocks

Construction – Access Door

Minimum Wall Thickness – 0.078"

Depth – 1 3/8" w/5/8" Blinds – 1 3/4" w/1" Blinds

Design – Flush w/ Interior Frame, Tubular

Fabrication – Mitered, Epoxied & Crimped w/Alum Corner Blocks Hinged With Concealed Locks Lift-Off With Concealed Locks (Size)

Weather-Stripping

Compression EPDM Bulb

Hardware

Primary Operable – Concealed Locks, Hinges, Single Blind Tilt Control Knobs

Glazing

Blinds – 5/8" or 1" Slats

Location – Factory

Method – Structural Tape - Outside Glazed

Type – 1/4" interior

Finish

As Specified – Anodized or Painted

Warranty

As Specified – 2, 5 or 10 Years