


ArmorDefend™ STOREFRONT - WINDLOAD CHARTS

Data is based on deflection limitations in accordance with AAMA TIR-A11 of L/175 up to 13'-6" and L/240 +1/4" above 13'-6", with a maximum deflection of 1 1/4". All curves reflect single span conditions, unless noted otherwise.


These curves reflect the limiting value for mullions with horizontals and are based on allowable windload stress for T6 aluminum (15,000 psi) and A36 steel (20,000 psi).

A 4/3 increase in allowable stress is not reflected in these curves. For special applications not covered by these curves, please consult your local Oldcastle BuildingEnvelope® facility for assistance.


FG-3495 / FG-3514




I = 3.328
S = 1.479




FG-3595 / FG-3514




I = 6.044
S = 2.686



FG-3328 / FG-3329



I = 4.100
S = 1.803




FG-3156 / FG-3514



FG-3155

I = 3.447
S = 1.532



ArmorDefend™ STOREFRONT - DEAD LOAD CHARTS

Data is based on maximum deflection of 1/8" at the center of an intermediate horizontal or 1/16" at center of transom bar above entrance. All curves are calculated for 1" thick ArmorGarde™ insulating glass (8.0 PSF) supported on two setting blocks at 1/4 or 1/8 point loading locations.

These curves are based on allowable windload stress for T6 aluminum (15,000 psi).

A 4/3 increase in allowable stress is not reflected in these curves. For special applications not covered by these curves, please consult your local Oldcastle BuildingEnvelope® facility for assistance.

