



HEAT

ThermaStack™ Storefront
Hot or cold, keep out unwanted guests.

ThermaStack™ Storefront



Insulate your project from heat, cold, and headaches.

Our thermal front set storefront system is a triple threat: easy to install, aesthetically pleasing, and energy-efficient. Inspired by our popular FG-3000 storefront series, it's designed to help you complete any job to the most exacting standards. For dependability down to the last detail, remember one name: ThermaStack™

Performance

ThermaStack™ provides the right performance for the job.

- Water: 8 PSF per ASTM E331
- Structural: 4' x 10' @ 40 PSF per ASTM E330
- Thermal: U-Factor = 0.36, CRF (frame) = 71 (with Solarban 70 Air Filled)
- Air infiltration: 0.06 cfm/sf at 6.24 PSF
- NFRC simulations and CMAST files available

Installation

To save you time and money, we engineer every detail of ThermaStack™ to make installation easier.

- Front Set Stack means simpler field installation with no notching required
- Continuous head and sill receptors facilitate easier, faster fabrication and installation
- Snap-in head and sill receptor inserts hold square-cut vertical members in place
- Interior and exterior glazing options available

Aesthetics

ThermaStack™ increases design appeal with our refined aesthetics.

- Front Set Stack provides a flush-glaze installation for a cleaner exterior appearance
- Available in painted and anodized finishes
- Smaller 2" sightlines

For More Info

Contact your Oldcastle BuildingEnvelope® representative, learn more online at OBE.com, or call us at 1-866-OLDCASTLE (653-2278).

